

LIGHTDISC

design Alberto Meda / Paolo Rizzatto, 2002

**LUCE
PLAN**

Type:	Wall/ Ceiling		
Light source:	D41/32.22	22W FSC T5 2GX13	EEL: A
	D41B/32.22		
	D41/40.55	55W FSC T5 2GX13	EEL: A
	D41 B/40.55		
	D41/40.55 D		
	D41/40.40E	40W FSC T5 2GX13	EEL: A

Product use: Indoor, Outdoor

Materials: Unbreakable, watertight polycarbonate

Colors: Structure in metallized, transparent, white
Front finishes in opaline, trasparent

Description: Sealed, ultra-light, slender, this fitting follows the circular shape of fluorescent lamps. Its minimal depth allows it to be fitted to ceilings or walls while appearing built-in. Metallic and trasparent finishes allow different modulations of light.

Certifications: **IP65**


Insulation class:  (D41/40.32 version requires functional earthing) 

Awards: Compasso d'Oro ADI Milano 2004, selection

Reference code:	D41/32.22	1D41PI220000	trasparent
		1D41PI220019	metallized
		1D41PI220002	white
	D41B/32.22	1D41PI22B000	trasparent
		1D41PI22B019	metallized
		1D41PI22B002	white
	D41/40.55	1D4100550000	trasparent
		1D4100550019	metallized
		1D4100550002	white
	D41B/40.55	1D410055B000	trasparent
		1D410055B019	metallized
		1D410055B002	white
	D41/40.55 D	1D410055D000	trasparent
		1D410055D019	metallized
		1D410055D002	white
	D41/40.40E	1D410040E000	trasparent
		1D410040E019	metallized
		1D410040E002	white



D41/32.22



D41/40.40E - D41/40.55 - D41/40.55D

