



7 W

230V

n°	W		 (lm)	 (cd)	 (°)	Ra	 (° K)	 (lm/W)	 (mm)	 (mm)	 (g)			
MM 14122i BR0707i	7	GU10	nvt	-	90	82	2700K	15.000	50	65	45	-	60 (10)	 4 020856 141227

Omgevingstemp. /Temp. ambiente -10 °C > + 40 °C



9 W

230V

n°	W	 (lm)	 (°)	Ra	 (° K)	 (h/N)	 (mm)	 (g)			EAN Barcode		
MM 14132i BR0709i	9	GU10 nvt	-	90	82	2700K	15.000	50	76	45	-	60 (10)	 4 020856 141328
MM 14134i BR0709i	9	GU10 nvt	-	90	82	4000K	15.000	50	76	45	-	60 (10)	 4 020856 141340

Omgevingstemp. /Temp. ambiente -10 °C > + 40 °C



11 W

230V

n°	W						Ra								EAN Barcode
MM 14142i BR0711i	11	GU10	nvt	-	90	82	2700K	15.000	50	76	54	-	60 (10)		
MM 14144i BR0711i	11	GU10	nvt	-	90	82	4000K	15.000	50	76	54	-	60 (10)		

Omgevingstemp. /Temp. ambiente -10 °C > + 40 °C



Luminous Intensity in cd

MM14132i
MM14132i + MM14134i
MM14142i + MM14144i

